

Teknik Özellikler



		SMC-2025	SMC-2063	SMC-4025	SMC-4040	SMC-4063	SMC-4100
Kutup Sayısı		2	2	4	4	4	4
Kontak Yapısı		2 NO	2 NO	4 NO	4 NO	4 NO	4 NO
Anma Akımı (AC-1 kullanım sınıfında)		25	63	25	40	63	100
Anma Yalıtım Gerilimi Ui		500 V AC	500 V AC	500 V AC	500V AC	500V AC	500V AC
Anma Darbe Gerilimi Uimp		2.5kV (12/24/48VAC için 4kV)	2.5kV (12/24/48VAC için 4kV)	2.5kV (12/24/48VAC için 4kV)	2.5kV (12/24/48VAC için 4kV)	2.5kV (12/24/48VAC için 4kV)	2.5kV (12/24/48VAC için 4kV)
Bobin Gerilimi		230V AC, 230V AC/ DC Ortak Bobin 24V AC/DC Ortak Bobin	230V AC, 230V AC/ DC Ortak Bobin 24V AC/DC Ortak Bobin	230V AC, 230V AC/ DC Ortak Bobin 24V AC/DC Ortak Bobin	230V AC, 230V AC/ DC Ortak Bobin 24V AC/DC Ortak Bobin	230V AC, 230V AC/ DC Ortak Bobin 24V AC/DC Ortak Bobin	230V AC, 230V AC/ DC Ortak Bobin 24V AC/DC Ortak Bobin
Güç tüketimi	Tutma	2.99VA	4.37VA	4.14VA	7.13VA	7.13VA	13VA
	Çekme	11.5VA	31.05VA	31.05VA	48.3VA	48.3VA	106VA
Elektriksel Ömür		100.000	100.000	100.000	100.000	100.000	100.000
Mekanik Ömür		1.000.000	1.000.000	1.000.000	1.000.000	1.000.000	1.000.000
Çalışma Sıcaklığı		-5°C~+60°C	-5°C~+60°C	-5°C~+60°C	-5°C~+60°C	-5°C~+60°C	-5°C~+60°C
Depolama Sıcaklığı		-40°C~+70°C	-40°C~+70°C	-40°C~+70°C	-40°C~+70°C	-40°C~+70°C	-40°C~+70°C
Koruma Sınıfı		IP20	IP20	IP20	IP20	IP20	IP20
Yardımcı Kontak Opsiyonları		1NO+1NC	1NO+1NC	1NO+1NC	1NO+1NC	1NO+1NC	1NO+1NC

Modüler Kontaktörler için Yardımcı Kontak



	Kontak Yapısı	Sipariş Kodu
SMC-YK	1 NO +1 NC	SMCYK

Boyutlar



SMC-2025





SMC-4063



SMC-2063



SMC-4100



SMC-4025

